



SAFETY DATA SHEET

DIBUTYLMAGNESIUM IN HEXANES

1. Identification of the Substance/Mixture and of the Company/Undertaking:

- 1.1 **Product Identifier:** Dibutylmagnesium in hexanes
1.1.1 **Substances** Not applicable
1.1.2 **Mixture name:** Dibutylmagnesium in hexanes
1.2 **Relevant Identified Uses of the Substance or Mixture and Uses Advised Against:**
Industrial Manufacturing
Only to be supplied for industrial uses
For use only as a chemical intermediate under strictly controlled conditions
1.3 **Details of the Supplier of the Safety Data Sheet**

North America
FMC Corporation
2801 Yorkmont Road, Suite 300
Charlotte, NC 28208
Phone: +1.704.426.5300
Fax: +1.704.426.5370
1.888.lithium

Europe
FMC Chemicals
Commercial Road
Bromborough, Merseyside
CH62 3NL, England
Phone: +44.151. 334.8085
Fax: +44.151.482.7361

Asia Pacific
FMC Asia Innovation Center
No 3 Building No. 4560
Jinke Road
Shanghai, China 201203
T: +86.21.2067.5888

Email: lithium.info@fmc.com
Web: www.fmclithium.com

1.4 **Emergency Telephone Number:**

North America
CHEMTREC: +1.800.424.9300
+1.703.527.3887
Plant: +1.704.629.5361
Medical: +1.303.595.9048

Europe
24 hr Specialist advice number:
CHEMTREC: +44 870 8200418

Asia Pacific
Phone: +86.21.2067.5888

2. Hazards Identification

- 2.1 **Classification of the Mixture:**
2.1.1 GHS Classification [EC Regulation No 1272/2008 and US OSHA regulations]
Water reactive; Category 1
Flammable liquid; Category 2
Skin corrosive; Category 1B
Eye Damage, Category 1
Aspiration toxicity; Category 1
Reproductive toxicity; Category 2
Specific target organ systemic toxicity – SE Category 3
Specific target organ systemic toxicity – RE; Category 2
Hazardous to the aquatic environment – Chronic; Category 2
2.2.2 EC: Classification according to 67/548/EEC or 1999/45/EC [DSD/DPD]
F, R14/15, C, R34; Xn, R 65, R67, R48/20; Repr Cat. 3, R62; N R51/53

2.2 **Label Elements:**
 2.2.3 **Hazard Pictograms:**



2.2.4 **Signal Word:**
Hazard Statement(s):

Danger
 In contact with water releases flammable gases, which may ignite spontaneously. H260
 Causes severe skin burns and eye damage. H314
 Highly flammable liquid and vapour. H225
 May be fatal if swallowed and enters airways. H304
 May cause drowsiness or dizziness. H336
 Suspected of damaging fertility. H361f
 May cause damage to organs through prolonged or repeated exposure. H373
 Toxic to aquatic life with long lasting effects; H411

Precautionary Statement(s):

Handle under inert gas. Protect from moisture. P231 + P232
 Keep away from any possible contact with water, because of violent reaction and possible flash fire. P223
 Wear protective gloves/protective clothing/eye protection/ face protection. P280
 In case of fire: Use dry chemical for extinction. P370 + P378
 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P301 + P330 + P331
 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. P303 + P361 + P353
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P305 + P351 + P338
 Immediately call a POISON Center or doctor/physician. P310

2.3 **Other Hazards**

Reacts violently with water EUH014

3. Composition / Information on Ingredients

3.1 **Substances** Not applicable.

3.2 **Mixtures**

3.1.1 **GHS Classification [EC: Regulation No 1272/2008; US: OSHA regulations]**

Chemical Name	CAS #	EC No	EC Index No	REACH Reg No	Wt.%	Classification, Hazard Statement Codes
Dibutylmagnesium	39881-32-8	254-671-1	None	None	12 - 20	Water-react. 1 H260 Skin Corr. 1B H314
Diocylmagnesium	24219-37-2	246-087-0	None	None	2 - 5	Water-react. 1 H260 Skin Corr. 1B H314
Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich ¹	None	925-292-5	None	01-2119474209-33-0016	75-86	Flam. Liq. 2 H225 Skin Irrit. 2 H315 Asp. Tox. 1 H304 Repr. 2 H361f STOT SE 3 H336

						STOT RE 2 Aquatic chronic 2	H373 H411
--	--	--	--	--	--	--------------------------------	--------------

¹ Contains n-hexane, CAS# 110-54-3

Chemical Name	CAS #	EC No	Wt.%	Symbols	R-phrases
Dibutylmagnesium	39881-32-8	254-671-1	12 - 20	F C	R14/15, R34;
Diocetyl magnesium	24219-37-2	246-087-0	2 - 5	F C	R14/15, R34;
Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich ²	None	925-292-5	75-86	F; Xi; Xn; Repr.Cat.3; N;	R11 R38 R65, R67, R48/20 R62 R51/53

¹ Contains n-hexane, CAS# 110-54-3

(see Section 16 for R-phrases text)

4. First Aid Measures

4.1 Description of First Aid Measures

- EYES:** Immediately flush with water for at least 15 minutes, lifting the upper and lower eyelids intermittently. See a medical doctor or ophthalmologist immediately.
- SKIN:** Immediately flush with plenty of water while removing contaminated clothing and/or shoes, and thoroughly wash with soap and water. Obtain immediate medical attention. Contact a medical doctor if necessary.
- INGESTION:** Quickly wipe material from the mouth and rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. See a medical doctor immediately.
- INHALATION:** Remove to fresh air. If breathing discomfort occurs and persists, see a medical doctor. If breathing has stopped, give artificial respiration and see a medical doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms of over-exposure will typically be a result of the corrosive nature of the substance with discomfort to skin and if swallowed, local effects with discomfort to the mouth and GI tract. Inhalation of solvent vapours may lead to dizziness and impairment of normal functions.

4.3 Indication of any immediate medical attention and special treatment needed.

Notes to medical doctor:

Product is highly alkaline and is corrosive to the eyes, skin and mucous membranes. Consideration should be given to careful endoscopy as stomach or esophageal burns, perforations or strictures may occur. Careful gastric lavage with an endotracheal tube in place should be considered. Observation may be warranted. Treatment is controlled removal of exposure followed by symptomatic and supportive care.

5. Fire-Fighting Measures

- 5.1 **Extinguishing media** DO NOT USE WATER OR CARBON DIOXIDE. Use dry chemical.
- 5.2 **Special hazards arising from the substance or mixture**
- Hazardous combustion products** Magnesium oxide fumes, carbon monoxide, carbon dioxide.
- General Hazard** Water reactive. Flammable liquid.
- Properties contributing to**
- Flammability** Water reactivity of product, and volatility of solvents.
- Flashpoint** Not available for formulation. The flashpoint of hexane is -26 C°.
- Flammable limits in air** Not available for formulation. For hexane: Upper: 7.7 wt% Lower: 1.2 wt%
- Auto ignition temperature** Not available.
- Sensitivity to static discharge** Yes
- Sensitivity to static impact** Not applicable

5.3 Advice for fire-fighters

Wear full protective clothing and self-contained breathing apparatus (SCBA) approved for fire fighting. This is necessary to protect against the hazards of heat, products of combustion and oxygen deficiency. Do not breathe smoke, gases or vapours generated.

COMMENTS:

(See Section 10, Stability and Reactivity)

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Before cleanup measures begin, review the entire SDS with particular attention to Section 2, Hazards Identification; and Section 8, Exposure Controls/Personal Protection. Remove all sources of ignition.

Spilled material can catch fire spontaneously on contact with air, moisture, acids or oxidizing materials.

6.2 Environmental precautions

Contain spill. Do not wash into drains. Dispose of at qualified waste disposal facility.

6.3 Methods and material for containment and cleaning up

Remove all sources of ignition. Spilled material can catch fire spontaneously on contact with air, moisture, acids or oxidizing materials. Cover spill with dry extinguishant. **DO NOT USE WATER OR CARBON DIOXIDE.** Contain spill with absorbant. Expose to air until solvent has dissipated. Sweep up and place in approved transport container. Dispose of waste according to local and Federal laws and regulations.

6.4 Reference to other sections

Before cleanup measures begin, review the entire SDS with particular attention to Section 2, Hazards Identification; and Section 8, Exposure Controls/Personal Protection.

6.5 Additional information

Not specified.

7. Handling and Storage

7.1 Precautions for safe handling

KEEP AWAY FROM WATER, AIR AND OXIDIZING MATERIALS. Wear a face shield with either chemical splash goggles or safety glasses. Use in a closed system under argon or nitrogen.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Store away from other flammable or combustible materials. Protect storage container from leaks and physical damage.

7.3 Specific end use(s)

For use only as a chemical intermediate under strictly controlled conditions

8. Exposure Controls / Personal Protection

8.1 Control parameters

Note that DNELs and PNECs have not been derived for dibutylmagnesium as it is used as a strictly controlled transported intermediate

DNEL Hexanes:

Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich

Long-term exposure, systemic, inhalation 93 mg/m³

Long-term exposure, systemic, dermal 13 mg/kg/day

PNEC Hexanes:

Not determined for the registration process

Estimated freshwater PNEC 0.05 mg/l using default factor 100.

EXPOSURE LIMITS

Chemical Name	EU		EH40 (UK WEL)		USA (ACGIH)		USA (OSHA)	
	TWA	STEL	TWA	STEL	TWA	STEL/Ceiling	PEL	STEL/Ceiling
n-Hexane	none*		20 ppm	72 mg/m ³	50 ppm		50 ppm	

8.2 Exposure controls

Refer to appropriate Exposure Scenarios

Engineering controls:

Use in closed system under argon or nitrogen. If personal contact can occur, use local exhaust ventilation (explosion-proof), to keep airborne concentrations below exposure limits.

Personal protective equipment

Eyes and Face:

Face shield with either chemical splash goggles or safety glasses.

Respiratory:

Wear a respirator approved for protection against organic vapours and mists when adequate ventilation is not available

US: NIOSH or MSHA approved

Europe: CEN Class A type

Protective Clothing:

Gloves: Nitrile (typical permeation breakthrough time >480 minutes)

These glove recommendations should not be used as the absolute basis for glove selection. Actual in-use conditions may vary glove performance from the controlled conditions of laboratory tests. Factors such as concentration and temperature, glove thickness and glove reuse, may affect performance. Other glove requirements, such as length, dexterity, cut, abrasion, puncture and snag resistance, or glove grip need to be considered in making your final selection. For flammable products, the recommended gloves provide chemical but not fire protection

Other: Flame resistant aramid fibre (Nomex® or equivalent. Nomex® is a registered trademark of E. I. du Pont de Nemours and Company)

Work Hygienic

Quick-drench eyewash and safety shower.

Practices:

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:

Clear, water-white to pale yellow liquid

Odor:

Gasoline-like

Odor threshold:

Not available

pH:

Reacts violently with water giving mixture with pH >12

Melting point:

Hexane: -95. C°

Boiling point:

Hexane: 62-69 °C

Flash point:

Not applicable for formulation. The flashpoint of hexane is -26 °C.

Evaporation rate(butyl acetate = 1):

7.1 – 8.4 (hexane)

Flammability:

Water reactive material in flammable liquid solvent

Flammable limits:

Not applicable for formulation. For hexane: Upper: 7.7 wt%
Lower: 1.2 wt%

Vapor pressure:

Hexane: 5.6 psi @ 38 °C

Vapor density (air = 1):

(air=1): Approximately 3 (hexane)

Specific gravity:

0.705 g/ml

Solubility in water:

Reacts violently with water

Partition coefficient n-octanol/ water:

Not available

Autoignition temperature:

Not available

Decomposition temperature:

Not available

Viscosity:

Not available

Explosive properties:

Not explosive

Oxidizing properties:

Not an oxidizer

9.2 Other information

Self-reactive properties

Does not meet classification criteria.

Pyrophoric properties

Does not meet classification criteria.

Self-heating properties

Does not meet classification criteria.

Water reactive properties

Dibutylmagnesium in hexane is a Category 1 water reactive material.

Corrosive to metals

Does not meet classification criteria.

Molecular weight:

138.4 (dibutylmagnesium)

10. Stability and Reactivity

10.1	Reactivity	Reactive with water and damp air
10.2	Chemical stability	Stable if kept away from air and moisture.
10.3	Possibility of hazardous reaction	Reaction with water, air, oxidizers, acids to form magnesium hydroxide, butane gas.
10.4	Conditions to avoid	Open air. Heat, sparks or flames
10.5	Incompatible materials	Water, damp air, carbon dioxide, lithium hydroxide.
10.6	Hazardous decomposition products	None

11. Toxicological Information

11.1 Information on toxicological effects

The mixture has not been tested, but properties can be predicted based on the properties of the two components

(a) acute toxicity	Dibutylmagnesium: Corrosive n-Hexane discriminating oral dose > 2000 mg/kg n-Hexane acute inhalation toxicity > 17.6 mg/l (5000 ppm) n-Hexane acute dermal toxicity > 2000 mg/kg
(b) skin corrosion/irritation	Classified as corrosive on the basis of dibutylmagnesium.
(c) serious eye damage/irritation	Classified as corrosive on the basis of dibutylmagnesium.
(d) respiratory/skin sensitisation	No components are considered to be potential sensitizing agents.
(e) germ cell mutagenicity	None of the components considered to be mutagenic.
(f) carcinogenicity	None on the components considered to be carcinogenic
(g) reproductive toxicity	n-Hexane suspected of damaging fertility or the unborn child.
(h) STOT-single exposure	n-Hexane may cause drowsiness.
(i) STOT-repeated exposure	n-Hexane may cause damage to the nervous system through inhalation
(j) aspiration hazard	n-Hexane may be fatal if swallowed and enters airways

Acute Effects From Overexposure:

No data available for the formulation. This product contains an alkyl lithium compound which is extremely reactive and corrosive to the skin, eyes (may cause blindness), nose, throat and stomach. Inhalation of vapors may cause dizziness, nausea, anesthesia, numbness, burning sensation and motor weakness in fingers and toes, incoordination, and headache. Low viscosity material--if swallowed may enter the lungs and cause lung damage.

n-Hexane: May cause peripheral nervous system disorder and/or damage. Blurred vision is associated with hexane polyneuropathy.

Chronic Effects From Overexposure:

No data available for product.

Hexane: Overexposure to n-hexane may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs. The neurotoxic effects of n-hexane vapour can be enhanced in rats by both methyl ethyl ketone (MEK) and lead acetate. The available information does not suggest that n-hexane is mutagenic. Negative results were obtained in most tests using live animals and relevant routes of exposure. n-Hexane has caused severe testicular damage in male rats at concentrations which have produced significant other toxicity.

Carcinogenicity Listings

EH40: Not listed.
IARC: Not listed.
NTP: Not listed.
OSHA: Not considered a carcinogen under OSHA.
ACGIH: Not listed.

12. Ecological Information

12.1 Toxicity:

The mixture has not been tested, but properties can be predicted based on the properties of the two components

The mixture is predicted to be toxic to aquatic organisms based on hexane

n-Hexane:

Fish 96h LC₅₀ 8.2 mg/l
Daphnia 48h EC₅₀ 4.5 mg/l
Daphnia reproduction toxicity, NOEC for reproduction 5 mg/l
Algae 96h IC₅₀ 3.1 mg/l

12.2 Persistence and degradability

Dibutylmagnesium: Dibutylmagnesium reacts violently with water to form butane and magnesium hydroxide.
Hexane: Hexane readily volatilizes, biodegrades in soil, water and wastewater treatment plants, adsorbs to organic matter in aquatic systems, has low mobility in soil.

12.3 Bioaccumulative potential

n-Hexane : Log BCF = 2.24 to 2.89

12.4 Mobility in soil

Solvents not expected to be mobile.

12.5 Results of PBT and vPvB assessment

A PBT and vPvB assessment has been undertaken for REACH and none of the components are considered to be of concern.

12.6 Other adverse effects

Due to the nature of the material and the specialist applications, this product is not considered to be a risk to the environment.

13. Disposal Considerations

13.1 Waste treatment methods

Disposal method:

Do not discharge to waste water systems.
Spent solvent may be sent for recovery or used as fuel if permitted under local regulations
Dispose of waste according to local and national laws and regulations.

14. Transport Information

14.1 <u>UN Number</u>	UN3399
14.2 <u>UN proper shipping name (IMDG, ICAO, ADR, DOT)</u>	Organometallic substance, liquid, water reactive, flammable, N. O. S. (dibutylmagnesium, hydrocarbon solution)
14.3 <u>Transport hazard class(es) (IMDG, ICAO, ADR, DOT)</u>	4.3, Dangerous when wet, (3, flammable)
14.4 <u>Packing group (IMDG, ICAO, ADR, DOT)</u>	I
14.5 <u>Environmental hazards</u>	Marine pollutant due to presence of hexane
14.6 <u>Special precautions for user</u>	None
14.7 <u>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</u>	None

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EUROPEAN UNION:

German Wassergefährdungsklasse (water hazard class)

dibutylmagnesium	not listed
n-hexane	2

UNITED STATES:

Section 311 Hazard Category (40 CFR 370):

Immediate (acute) health hazard, delayed (chronic) health hazard, fire hazard, reactive

Section 313 Reportable Ingredients (40 CFR 372):

This product contains hexane which is a substance subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986.
This information must be included in all SDS's that are copied and distributed for this material.

Section 302 Extremely Hazardous

Not listed

Substances (40 CFR 355):

CERCLA Hazardous Substance (40 CFR 302.4):

n-Hexane and hexanes are listed. The reportable quantity is 5000 pounds.

TSCA Sec 12b Export Notification:

This product is not subject to TSCA 12 (b) Export Notification Requirements.

NFPA Rating:

Health: 3 Flammability: 4 Reactivity: 3 Special: W

INTERNATIONAL INVENTORY STATUS:

<u>Inventory/Country</u>	<u>Product Status</u>
EINECS (EU)	Listed
TSCA (US)	Listed
ECL (Korea)	Listed
DSL (Canada)	Listed

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for dibutylmagnesium

16. Other Information

European Union:

R Phrases:

Highly flammable.	R11
Irritating to skin.	R38
Reacts violently with water, liberating extremely flammable gases	R14/15
Causes burns	R34
Harmful: may cause lung damage if swallowed	R65
Harmful: danger of serious damage to health by prolonged exposure through inhalation	R48/20
Possible risk of impaired fertility	R62
Vapours may cause drowsiness and dizziness	R67
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment	R51/53

List of Abbreviations used in this SDS:

PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent, very Bioaccumulative
PEC	Predicted environmental concentration
PNEC	Predicted no effect concentration
DNEL	Derived no effect level

Specific uses identified for Exposure Scenarios

None

REVISION SUMMARY: Revision 0. New SDS.

This SDS has been prepared to meet European Regulation (EC) No 1907/2006 [and No 1272/2008] requirements. type 4

Copyright 2016. FMC Corporation. All Rights Reserved. FMC and the FMC logo are trademarks of FMC Corporation.